

Easy: 1-2 hours

Athearn® Ready To Roll® P40 [AMD-103] & P42DC

To add a SoundTraxx Tsunami2 Digital Sound Decoder to your non-sound P40 [AMD-103] or P42DC model (announced in April 2003), you'll want to install a TSU-PNP GE decoder.



Since 2009, Athearn has provided the option of purchasing some of their models equipped with Tsunami sound. If you have a P40 [AMD-103] or P42DC model without sound that you would like to upgrade, purchase SoundTraxx P.N. 885014. This board is designed to simply replace the factory PCB that supplies power to the locomotive. You can complete the installation in one to two hours with no modification required to the model!



The Sound Upgrade



SoundTraxx Sound Decoder SoundTraxx Speakers SoundTraxx Accessories

TSU-PNP, P.N. 885014 \$110.95 28mm Square Mega Bass Speaker, P.N. 810131 \$11.95 30-gauge Wire, Purple, P.N. 810144 \$5.95 Shrink Tube Assortment, P.N. 810037 \$9.95

> **Total** \$138.80 (MSRP)

Other Tools & Supplies You Will Need

- 0.75mm Sheet Styrene 25-watt Soldering Iron Rosin Core Solder Wire Strippers Wire Cutters X-ACTO® Knife
- Metal Straight Edge
- **Dial Calipers**
- Miniature Screwdriver Set

- Aguarium Sealant/Silicone Liquid Plastic Cement
 - (TENAX-7R™ or equivalent)
- Kapton Tape **Small Pliers**
- Heat Gun or Blow Dryer